

Lutz Drum Pump Sets



– Now available –

Electric or Air Driven Drum Pump Sets for Flammables, Hazardous Locations

Consisting of:

Motor ME I 6 EX, Class I Group C&D, Class II Groups F&G (Explosion Proof) with 16 ft cord or MD2 air motor, pump tube SS 39" sealless, high volume rotor, 1" SS Barrel Adaptor, 1" SS Nozzle with swivel, 8 ft. Conductive Chemical Tubing with Conductive Fittings, Ground & Bonding wires, Wall Hanger



Type of motor:

ME I 6 (Ex)

MD2 Air motor (Ex)

Technical Data:

Max. Viscosity:	500 CPS	850 CPS
Max. Capacity:	18.5 GPM	18.5 GPM
Max. head:	33 ft.	33 ft.
Max. S.G.	1.3	1.6
Immersion depth:	39"	39"
Order-No.	0205-411-1	0205-411-2
Immersion depth:	47"	47"
Order-No.	0205-412-1	0205-412-2
Immersion depth:	55"	55"
Order-No.	0205-413-1	0205-413-2



Electric or Air Driven Drum Pump Sets for Thin-bodied Oils and Diesel Fuel

Consisting of:

Motor B36 with 16 ft cord or MD2 air motor, pump tube ALU 39" sealless, high head impeller, 316 stainless steel shaft, PP Barrel Adaptor, 1" aluminium Nozzle with swivel, 8' PVC Hose, Hose Clamps, Wall Hanger



Type of motor:

B36

MD2 Air motor

Technical Data:

Max. Viscosity:	500 CPS	1100 CPS
Max. Capacity:	15.9 GPM	15.9 GPM
Max. head:	68 ft.	68 ft.
Max. S.G.	1.4	1.6
Immersion depth:	39"	39"
Order-No.	0205-301-1	0205-301-2
Immersion depth:	44"	44"
Order-No.	0205-302-1	0205-302-2
Immersion depth:	55"	55"
Order-No.	0205-303-1	0205-303-2

