

# 'PURE' - FDA / 3A Lutz Drum Pump Sets



## PURE Lutz Pump Set for FDA / 3A applications, non Ex application

### Consisting of:

Electric or air driven motor, 8 ft. Food Grade Hose 1", non-conductive  
Tri-clamp connections, 39" / 47" / 55", high-head ETFE impeller,  
2" PP drum adapter, SS Nozzle / EPDM seal, with swivel, Wall hanger



**B55-T**



**MD2 Air motor**

### Type of motor:

### Technical Data:

Motor:	120 V, 0.68 hp, TEFC	0.54 hp, 87 psi, 32 CFM
Max. Viscosity:	1000 CPS	1100 CPS*
Max. Capacity:	13.2 GPM	13.2 GPM
Max. spec. Gravity:	1.6	1.6

Immersion depth:	39"	39"
Order-No.	P206-411-1	P206-411-2
Immersion depth:	47"	47"
Order-No.	P206-412-1	P206-412-2
Immersion depth:	55"	55"
Order-No.	P206-413-1	P206-413-2



Tri-clamp connections



## PURE Lutz Pump Set for FDA / 3A applications, EX proof applications

### Consisting of:

Electric or air driven motor, 8 ft. Food Grade Hose 1", conductive, Tri-clamp  
conductive connections, 39" / 47" / 55", high-head ETFE impeller, 2" SS drum adapter,  
SS Nozzle / EPDM seal, with swivel, Wall hanger, Ground & Bonding wires



**ME I 6 (Ex)**



**MD2 Air motor**

### Type of motor:

### Technical Data:

Motor:	120 V, 0.68 hp, TEFC	0.54 hp, 87 psi, 32 CFM
Max. Viscosity:	750 CPS	1100 CPS*
Max. Capacity:	13.2 GPM	13.2 GPM
Max. spec. Gravity:	1.6	1.6

Immersion depth:	39"	39"
Order-No.	P206-511-1	P206-511-2
Immersion depth:	47"	47"
Order-No.	P206-512-1	P206-512-2
Immersion depth:	55"	55"
Order-No.	P206-513-1	P206-513-2



Tri-clamp connections



\*Max. 760 CPS is with hand nozzle