‘PURE’ - FDA / 3A
Lutz Drum Pump Sets

PURE Lutz Pump Set for FDA / 3A applications, non Ex application

Consisting of:
Electric or air driven motor, 8 ft. Food Grade Hose 1”, non-conductive
Tri-clamp connections, 39” / 47” / 55”, high-head ETFE impeller,
2” PP drum adapter, SS Nozzle / EPDM seal, with swivel, Wall hanger

Type of motor:	**B55-T**	**MD2 Air motor**
Technical Data:		
Motor:	120 V, 0.68 hp, TEFC	0.54 hp, 87 psi, 32 CFM
Max. Viscosity:	1000 CPS	1100 CPS*
Max. Capacity:	13.2 GPM	13.2 GPM
Max. spec. Gravity:	1.6	1.6
Immersion depth:	39“	39“
Order-No.	P206-411-1	P206-411-2
Immersion depth:	47“	47“
Order-No.	P206-412-1	P206-412-2
Immersion depth:	55“	55“
Order-No.	P206-413-1	P206-413-2

Tri-clamp connections

02-10

PURE Lutz Pump Set for FDA / 3A applications, EX proof applications

Consisting of:
Electric or air driven motor, 8 ft. Food Grade Hose 1”, conductive, Tri-clamp conductive connections, 39” / 47” / 55”, high-head ETFE impeller, 2” SS drum adapter, SS Nozzle / EPDM seal, with swivel, Wall hanger, Ground & Bonding wires

Type of motor:	**ME I 6 (Ex)**	**MD2 Air motor**
Technical Data:		
Motor:	120 V, 0.68 hp, TEFC	0.54 hp, 87 psi, 32 CFM
Max. Viscosity:	750 CPS	1100 CPS*
Max. Capacity:	13.2 GPM	13.2 GPM
Max. spec. Gravity:	1.6	1.6
Immersion depth:	39“	39“
Order-No.	P206-511-1	P206-511-2
Immersion depth:	47“	47“
Order-No.	P206-512-1	P206-512-2
Immersion depth:	55“	55“
Order-No.	P206-513-1	P206-513-2

*Max. 760 CPS is with hand nozzle

Tri-clamp connections

02-10

Lutz Pumps, Inc. · 1160 Beaver Ruin Road · Norcross, GA 30093-4898 · Phone (770) 925-1222 (800) 843-3901 · Fax: (770) 923-0334
e-mail: info@lutzpumpsamerica.com · www.lutzpumps.com